




Охладители таблеточного типа

ТИП ОХЛАДИТЕЛЯ	Размеры (Ширина x Длина x Высотат), mm (Без токоотвода)	Масса, kg (Без токоотвода)	Диаметр контактной поверхности, mm	Тепловое сопротивление, °C/Вт(мощность рассеивания, Вт)		Перепад давления IPaV _{cf} = 6m/s	Конфигурация профиля
				V _{cf} = 0	V _{cf} = 6m/s		
0-232	70x80x172max (70x80x100)	1,6(1,30)	42	1,120 (80)	0,355	18	
0-242	110x110x172max (110x110x100)	2,400(2,100)	55	0,670 (150)	0,236	25	
0-342	126x150x200max (126x150x130)	3,500(3,358)	58	0,530 (150)	0,170	20	
0-123	150x100x122max (100x100x122)	2,000(1,840)	22	0,710 (120)	0,212	20	
0-143	185x150x125max (135x150x125) 185x150x120max (135x150x120)	3,000(2,670)	42	0,500 (120)	0,125	30	
0-243	230x150x170max (170x150x170)	5,800(5,000)	42	0,280 (220)	0,080	30	
0-153	230x150x176max (170x150x176)	6,000(5,200)	55	0,280 (220)	0,075	30	
0-343	230x150x145max (170x150x145) 230x150x150max (170x150x150)	5,300(4,500)	42	0,355 (220)	0,100	30	
IEAL. 065167. 006-13	230x150x145max (170x150x145) 230x150x150max (170x150x150)	4,700(3,900)	42	0,365 (220)	-	-	

0-253	230x150x145max (170x150x145) 230x150x156max (170x150x156)	5,500(4,700)	55	0,355 (220)	0,100	30	
IEAL. 065167. 006-13	230x150x145max (170x150x145) 230x150x156max (170x150x156)	4,900(4,100)	56	0,365 (220)	-	-	
0-353	230x150x156max (170x150x156)	5,700(4,900)	55	0,355 (220)	0,100	30	
DJIC. 648474. 001	170x250x170max	8,500	76	0,2 (275)	0,053	35	